



DURAZIP



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Less than 1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL SPECIFICATIONS

Material:	PC/PBT
Mounting System:	Stainless Steel Cable
Color:	Custom Logo and Colors Available

OPERATIONAL SPECIFICATIONS

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
IK Impact Rating:	IK10
Water and Ice Proof:	Yes

PRODUCT DIMENSIONS

Weight:	40g/ 1.4 oz
Dimensions:	1.4" x 1.2"
Thickness:	0.7"
Cable:	Diameter 3.0 mm Length 12"



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Valves, Pipes & Industrial Equipment

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details please email sales@infochip.com or call Toll Free 1-877-747-CHIP (1-877-747-2447).

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com