



CHAIN SLING TAG



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Less than 1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	Stainless Steel or Aluminum
Mounting System:	Chain, Hook, Tie, Rope
Color:	Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	300°F/ 150°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	300°F/ 150°C
Continuous Max Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	84g / 2.96 oz
Dimensions:	4.89" x 1.5"
Thickness:	.125"



RECOMMENDED TAG APPLICATIONS

Lifting: Wire Rope and Chain Slings

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details please email sales@infochip.com or call Toll Free 1-877-747-CHIP (1-877-747-2447).

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com